

Instruction

The mini Smart Gateway supports Wi-Fi, Bluetooth Sig Mesh and Zigbee 3.0 multi-protocol communication. This allows it to seamlessly connect with various wireless accessories through the DNAKE Smart Life App including smoke sensors, temperature and humidity sensors, door and window sensors, motion sensors, water leak sensors, gas sensors and smart button etc. The versatility of the Smart Gateway enables users to create a comprehensive and interconnected smart home ecosystem.

Smart Hub



Key Features

- Adopts standard ZigBee 3.0 protocol and Bluetooth Sig Mesh standard protocol, good compatibility
- Support up to 32 Zigbee sub-devices
- Support customized scenes, customized smart linkage
- Compact and lightweight design

Technical Parameters

- Model Name: MIR-GW200-TY
- Communication: Zigbee 3.0, Bluetooth Sig Mesh, Wi-Fi 2.4GHz
- Zigbee Communication Distance: <=100 m (Open area)
- Power Supply: Micro USB DC5V
- Working Current: <1A
- Adapter: 110V~240VAC, 5V/1A DC
- Working Voltage: 1.8V ~ 3.3V
- Working Temperature: -10°C to 55°C
- Working Humidity: 10% - 90% RH (Non-condensing)
- Status Indicator: 2 LED (Wi-Fi + Zigbee / Bluetooth)
- Operation Buttons: 1 button (reset)
- Dimension: 60 x 60 x 15 mm